



CSX

FULLY AUTOMATIC RANDOM SIDEDRIVE

The BestPack™ CSX Series Fully Automatic Random Carton Sealer's advanced engineering provides the high speed output, and are built for rugged dependability. The CSX design uses three independent operating stations that include the Centering Station, Folding Station, and Sealing Station. For operational dependability and performance, maintenance free oil-less air cylinders are used. These features along with others in our CSX Series set BestPack apart from others in the marketplace. These sealers are designed to meet all your operator free random carton sealing applications.

All BestPack units are available in our standard baked enamel finish or food grade 304 stainless steel for 21 CFR 110 compliance. Custom sizes available for your application.



NO OPERATOR REQUIRED



RANDOM CARTONS



TOP & BOTTOM SEAL

110 VOLTS 60 HZ

Power Requirements

UP TO 12 CPM

Speed


100 PSI

Air Requirements

1,320 LBS

Shipping Weight

CARTON RANGE



Length (min. - max.)
(9.0" - 25.0")

Width (min. - max.)
(6.3" - 20.5")

Height (min. - max.)
(5.5" - 22.0")

Specifications based on CSX22-2H

STANDARD FEATURES

- Heavy Duty 3mm CNC Cut and Welded Frame Including Upper Welded Legs
- Omron PLC Logic
- Independent Random 3-stage Operation: Centering, Flap Folding, & Sealing
- Random Side Belt Drive with High Speed Motors
- Random Upper Side Compression Rollers
- Interlock Safety Gates
- Capable of Interchanging 2" or 3" BestPack High Speed Tape Heads
- Heavy Duty Maintenance Free Oil-less Air Cylinder Electrical Panel and Air Adjustments are Left Justified (Unless otherwise ordered)
- Tape Roll Lengths: 1,000 yd. & 1,500 yd.
- Low Tape/No Tape on Carton/No Cut Sensors & Alarm with Three Color Warning Light
- UL Approved Electrical Parts
- Heavy Duty Casters
- Low Tape/No Tape on Carton/No Cut Sensors & Alarm with Three Color Warning Light
- Exclusive 2" or 3" Pop-out Pressure Sensitive "High Speed" Tape Head with Patented Tab Adjustment and Noise Reduction Arm

OPTIONS

- Food Grade 304 Stainless Steel
- Retractable Top or Bottom Tape Heads
- Touch Screen Human Interface
- User Specified PLC Brand
- Exit Conveyor

VERSION 3.1_0120

QUALITY • INNOVATION • COMMUNITY

EXTRA ACCESSORIES TO IMPROVE EFFICIENCY



SPARE PARTS KIT

Spare Parts Kits may vary based on machine
Minimize downtime with BestPack's Spare Parts Kit.



SPARE TAPE HEAD

Order a spare tape head with your machine to minimize down time. Having a spare will allow you to drop in a tape head with a new roll of tape in no time!



LONG INFEED/EXIT CONVEYOR W/ L-BRACKET STABILIZER

This 39.5" long conveyor is a great work platform and allows for staging of cartons on the infeed and the exit.



FOOD GRADE 304 STAINLESS STEEL

This machine is available in 304 stainless steel which is food grade safe for food applications.



CARTON SEALING TAPE

Put high quality tape on your BestPack Carton Sealer. Make sure to order machine length rolls for your new carton sealer.

POPULAR CSX MODELS

Please refer to comparison chart for complete list of models.

MODEL	MACHINE DIMENSIONS LENGTH x WIDTH x HEIGHT	CARTON RANGE* LENGTH (min. - max.) x WIDTH (min. - max.) x HEIGHT (min. - max.)	CONVEYOR HEIGHT HEIGHT (min. - max.)	CARTONS PER MIN.	SHIPPING WEIGHT (LBS)
CSX22-2H 2" Tape Head	(95.8") x (40.0") x (90.5")	(9.0" - 25.0") x (6.3" - 20.5") x (5.5" - 22.0")	Determined at the time of order	Up to 12	1320
CSX22-3H 3" Tape Head	(95.8") x (40.0") x (90.5")	(9.0" - 25.0") x (6.3" - 20.5") x (5.5" - 22.0")	Determined at the time of order	Up to 12	1320

Information subject to change without notice.

* Outside Dimensions Only
All Models Available in Food Grade 304 Stainless Steel

BestPackTM
the total tape sealing solution

DOVERCO
Strategic. Packaging.

2111 32nd Avenue, Montreal, Quebec H8T 3J1
Tel: (514) 420-6060 • Fax: (514) 420-6015
250 Trowers Road, Unit 7, Vaughan, Ontario L4L 5Z6
Tel: (289) 256-2141 • Fax: (289) 256-2142
Toll Free: 1-800-363-0697 • www.doverco.ca • sales@doverco.ca