

cartoning machines

You may be looking somewhere else but she will always be working for you and even without you. Compact outside. Spacious and accessible inside. The horizontal style cartoning machine for American cartons. Compact size, high speed, motorized product feeding, versatile in changing format.

>> general features

The in-line cartoning machine for boxes is designed for installation downstream of the packaging lines in order to gather the products out of the packaging machine in groups and stack them at different height. The number and depth of the product rows is adjustable. The products, bundled together by the loader equipped with a stacker unit, are pushed and packed inside a carton box and closed by the same machine. After filling, the boxes are conveyed to the outlet and the machine folds the top case flaps and closes them with tape on the two sides. (optional: closing with glue using the Hot Melt system).

>> specific features

The cartoning machines strengths are: Compact size, high speed, motorized rotary pushing feeder (non pneumatic). Quick box size change and user-friendly access to all adjustable parts. Actuators moving on dovetail rails and recirculating ball bearings blocks. Plc controlled.

DOVERCO
Strategic. Packaging.

2111 32nd Avenue, Montreal, Quebec H8T 3J1
Tel: (514) 420-6060 • Fax: (514) 420-6015


250 Trowers Road, Unit 7, Vaughan, Ontario L4L 5Z6
Tel: (289) 256-2141 • Fax: (289) 256-2142

Toll Free: 1-800-363-0697 • www.doverco.ca • sales@doverco.ca


>> details



Positive motorized. Automatic cartons opening and products insertion.



In feed conveyor with different loading systems depending on the products.



Blank picking system provided with motor.



Machine controlled by Siemens PLC and intuitive touch panel. Auto adjustable change of format.



New ergonomic design. All machine parts are fully accessible by innovative sliding or opening guards. The collation module can easily be separated from the case packer module for change over and.



Double operator position, thanks to rotary control panel.



Automatic case closing with tape or hot melt. Motorised side guides. Auto adjustable.



Canter level structure perfect for maintenance and cleaning.




High quality components, ISO certified.

GEOS-11/2015 - rettangolare.it

side load case packer

>> GEOS



PREFERRED PACKAGING ITALY
leader in the manufacturing packaging equipment


DM PACK

GD pack

GB

GEOS

side load case packer



>> technical features

Machine dimensions LxWxH	2990x3670x2198 mm
Carton dimension minimum LxWxH	300x200x200 mm
Carton dimension maximum LxWxH	600x400x400 mm
Weight	900 Kg
Speed	10 cartons/min

Cartoning machines for bigger sizes on request

>> Compact, robust, well-built. Motorized auto adjustable. Fast & simple change of format.

>> Siemens touch screen full automatic change over.

>> Accessibility: doors open in all machine's sides. Operator can easily maintain and enter. Optimal operability. Operator can work on both sides thanks to rotary touch screen.



>> Reduced size. High speed, up to 10 cartons per minute.

>> Side filling for cartons up to 800x1200 mm.